

CSM-Fab, Inc.

PO Box 448 5089 Rt. 60

Ceredo, WV 25507-0448 Phone: (304)429-6918 Fax: (304)429-6919

Duct Construction Standards for TDC 6" WG Pressure





CSM-Fab, Inc.

manufactures lined and unlined HVAC Duct from Galvanized metal, Stainless Steel, Paint Grip, aluminum and carbon steel according to SMACNA Standards in our union facility. All rectangular fabricated with duct is stiffening beads using state of the art equipment.

All 56&1/4" rectangular duct is fabricated with TDC seams formed directly into the metal to avoid leakage with TDC corners installed.

All duct and fittings are fabricated with Pittsburgh or welded as per your specifications and we can accommodate most any size of Fittings are duct. All fabricated in accordance with SMACNA standards with all accessories (TDC corners, Vane & Rail, etc.. Installed all nuts, bolts, gasket, and Cleat included).

6" TDC WG	RECTANGULAR DUCT CONSTRUCTION SCHEDULE				
POS.OR NEG	TDC STANDARD DUCTWORK				
DUCT DIMENSION	GAGE	JOINT	CTR	JTR	
10-18	24	TDC	NONE	NONE	
19-24	22	TDC	NONE	NONE	TDC = TRANSVERSE DUCT CONN
25-28	20	TDC	NONE	NONE	
29-42	24	TDC	YES	NONE	CTR=CENTER TIE ROD
49-54	20	TDC	YES	NONE	
55-60	22	TDC	YES	YES	JTR = JOINT TIE ROD
61-96	20	TDC	YES	YES	
97-UP	18	TDC	YES	YES	

